

ANEXO CONVOCATORIA

6/2017

RENGLONES

Renglón	Especificación Técnica	Imagen
	- LNL-2210 Intelligent Single Door Controller – PoE or12 VDC @ 900mA, size (5.5" (140mm) W x 2.75" (70mm) L x 0.96" (24mm) H, (rechargeable battery) 6 MB standard cardholder flash memory, 50,000 of Event memory, maximum of one door, two readers (entry and exit reader, On-board PoE Ethernet, two inputs (supervised/unsupervised), two outputs (NO/NC), power fault input and cabinet tamper monitors. Reader power 12VDC@ 650mA max, RoHS, CE, and UL 294 (pending) - 21P112 ProxPoint® Plus Proximity Reader 125 kHz Proximity Access Control Reader - LNL-CCK-1401L Lenel Time & Attendance real time display timer, with 1 inch LCD	
	- ST-2406-3A Fuente regulada 6, 12 o 24 VCC - 3 A	
	- GA1104 Gabinete metálico con ventilación	
	- TRAFO24V3A Trafo para fuente regulada 24vca 3 amp.	
	- B128 Batería 12v 7 Ah.	
	- Los productos tiene que ser nuevos y originales.	
	- Plazo de entrega 30 días habiles	
	-Todos los productos tendran que tener garantía por	



Universidad Nacional de Moreno

Renglón	Especificación Técnica	Imagen
	1 (un) año.	
	,	
	- Materiales para Cableado, Montaje y Conexionado de	
	Equipos	
	- Mano de Obra Instalación Física - Puesta en marcha HW + SW	
	- Ingeniería de Detalle y Documentación	
2		
2		